



TERMOD

SOMOS LA PLATA



Kipp & Zonen RT1 Rooftop Monitoring System

de producto:

0385900

CLP Precio:
Disponible

Contacto Termodinámica

The RT1 has been designed specifically for the commercial rooftop PV. For the best commercial rooftop PV monitoring it is advised to measure both the solar irradiation and the PV panel temperature. The rugged housing of RT1 simply fits to the corner or side of a PV panel and contains the digital electronics. It also houses a sensor that reliably measures the incoming plane of array solar irradiance. The plug-in temperature sensor is easily attached to the back of the panel. RT1 is the perfect solution for monitoring the efficiency of commercial rooftop PV installations. PV panel temperature has a significant influence on the output of the PV panels and shouldn't be mixed up with influences of e.g. soiling, cable losses and inverter losses.

ISO / IEC classification

ISO 9060 fast response Class C, with ISO / IEC 17025 calibration.

Minimized maintenance

No desiccant change for 5 years, with 5 years warranty.

Designed for rooftop PV applications
The RT1 fits to a corner of any PV solar panel, smart digital duo sensor, Irradiance and back panel temperature.

Especificaciones

Classification:	Fast response Class C (ISO 9060:2018)
Directional Response:	# 1.7 % (up to 55 ° with 1000 W/m² beam)
Exactitud espectral:	400 - 1100 nm
Grado de protección IP:	IP67
Humedad de operación:	0 - 100 %
Intervalo de mantenimiento y cartucho de secado:	Internal, no replacement necessary
Longitud de cable:	20 m
Material carcasa:	Aluminum, anodised
Non-linearity:	# 1% (0 - 100 W/m²)
Non-stability:	# 1% (change/year)
Peso:	500 g
PV Panel Temperature:	-20 °C - +100 °C, ±1 °C
Rango de temperatura de operación:	-40 - +80 °C
Salidas analógicas:	n.a.
Salidas digitales:	Modbus RTU 2-wire RS-485
Saturación irradiación:	2000 W/m² (Max.)
Sensibilidad:	n.a.
Temperature Correction:	# 3.5 % (-40 - +80 °C)
Tiempo de respuesta:	1 s (95 %)
Zero offset A:	none
Zero offset B:	none